

Lecture notes by Edward Loper

Course: CIS 570 (Modern Programming Language Implementation)

Professor: E Christopher Lewis

Institution: University of Pennsylvania

|| <http://www.cis.upenn.edu/~eclewis/cis570>

Monday, January 15, 2001

Assignments:

- midterm
- final
- small assignments
- reading summaries (1-page)
- group project

Group project... can i do anything with compilers/linguistics? ...

Wednesday, January 17, 2001

Notes:

- Contact E. re wpe?
- Add self to mailing list?

Notes:

- dunkumware.com ?
- st david sq? lancaster?

1 Data-flow analysis

1.1 Control Flow Graph (CFG)

diagram where nodes are commands and edges are possible transitions between commands.

1.2 Liveness

A variable is "live" on an edge $i \rightarrow j$ of a control flow graph iff the program's behavior at j or $\text{future}(j)$ depends on the value of the variable at node i .

If two variables are live at mutually exclusive edges, then they can share a register.

Liveness is a property that flows "backwards" through CFGs: find usages of v , and follow CFG backwards (on all paths) until you find a definition of v . All edges traversed are live.

1.3 Back to CFGs

CFGs have a number of properties. These properties "flow" through the CFG in specific ways. E.g., liveness flows backwards through the CFG. Other properties flow in different ways.

Terms

- out-edge: an edge leading out of a node
- in-edge: an edge leading into a node
- successor node: a node connected by an out-edge
- predecessor node: a node connected by an in-edge
- $\text{pred}[n]$ = set of predecessor nodes of n
- $\text{succ}[n]$ = set of successor nodes of n
- def: a node that defines a variable
- use: a node that reads a variable
- defs of a variable = set of nodes
- defs of a node = set of variables

1.4 Back to liveness

Fomal definition of liveness:

v is live on edge e iff:

1. $\exists p \in \text{paths from } e \text{ to a USE of } v$
2. p does not go through any DEF of v

Defs for liveness:

- a variable is live-in at a node if it is live on any of the node's in-edges.
- a variable is live-out at a node if it is live on any of the node's out-edges.

Finding liveness:

1. if $v \in \text{use}[n]$, then $v \in \text{live-in}[n]$
2. if $n1 \rightarrow n2$, $v \in \text{live-in}[n2]$, then $v \in \text{live-out}[n1]$
3. if $v \in \text{live-out}[n]$ and $v \notin \text{def}[n]$, then $v \in \text{live-in}[n]$

So: $\text{in}[n] = \text{use}[n] \cup (\text{out}[n] - \text{def}[n])$ $\text{out}[n] = \cup\{s \in \text{succ}[n]\} \text{in}[s]$

Finding it

iterate the in and out equations until we get convergence. to make it faster:

- make sure we compute things in the right order.. namely, backwards.
- only consider basic blocks

send email to listsrv about project?

2 SSA

SSA can be used to make UD and DU chains more sparse. SSA is an "alternate" program representation. memo to myself – can ssa be used in bytecode? last minute optimizations.. whee.

2.1 Alternate program representations

- can allow analyses and transformations to be simpler & more efficient/effective.
- may not be "executable"
- may make inefficient use of space

2.2 Static Single Assignment Form (SSA)

Idea: each assignment is to a uniquely named variable Property: each use has exactly 1 reaching def Effects: makes UD chains sparse

Transformation:

- rename each def
- rename uses reached by that def
- trivial for straight-line code
- for joins, we need a new operation ϕ . (special case: loops)

2.3 SSA vs UD/DU chains

Advantages of SSA:

- more compact
- easier to update/manipulate
- each use has only 1 def
- value merging is explicit
- eliminates "false" dependencies

3 Transforming to SSA

- Insert ϕ -functions
- Rename variables

3.1 Insert ϕ -functions

basic rule: If $x \rightarrow z$ and $y \rightarrow z$ converge at z , and x and y contain defs for v , then ϕ for v is inserted at z .

placing approaches:

- minimal = as few as possible, subject to basic rule
- briggs-minimal = minimal, but v must be live across some basic block. Intuition – if a variable v is assigned and used in the same basic block, and never used again, then don't bother with it.

- pruned = same, except dead ϕ 's not listed. this will have a subset of the ϕ functions of briggs-minimal.

Machinery

domination:

- $d \text{ dom } i$ if all paths from entry $\rightarrow i$ include d
- $(d \text{ sdom } i)$ iff $(d \text{ dom } i)$ and $(d \neq i)$

dominance frontier:

- dominance frontier of d is the set of nodes that are "just barely" not dominated by d .
- dominance frontier of a set of nodes is the union of the dominance frontiers of the nodes.
- to find dominance frontier: find set of nodes dominated by d , then go "one beyond" (including loop up to d but not loops to anything else that d dominates).
- dominance frontier nodes are nodes where value from d merges with some other value.

Using dominance frontiers

1. find dominance frontier of the defs of a var. Then add everything from the dominance frontier to the set of defs, and find the dominance frontier of that.. repeat.

Theorem: iterated dominance frontier = set of nodes that require ϕ -functions for v .

3.2 Rename Variables

4 Using SSA

4.1 Constant Propagation

- Simple: Constant for all paths through a program
- Simple sparse
- Conditional: Constant for all actual paths through a program
- Conditional sparse

5 Interprocedural Analysis

DLLs with summaries?

Tuesday, April 10, 2001